Truss Bracket 1-1/2 dia. tubes Model TB1500 - Anchors truss poles to mirror box, rotates to match angle - Machined from 1/4 in. thick aluminum angle **Includes:** - Knob stays with mirror box during transport 1 Bracket - Can be mounted on the inside or outside of mirror box 1 Knob - Fast on-off, slip fork over mounting stud, tighten knob 1 Tube connector - Reinforced plastic knob with steel insert 1 1/4-20 x 1 SS bolt - Black anodized finish - Weight: 2.9oz - 82g .049 & .060 wall thickness available **-**1/8 Tube connector and 1/4-20 -7/8 from mirror box to center of tube Stainless screw is included Wall of mirror box Tube bracket nests with tube for a rigid non-flexing 1/4-20 stud attached connection to mirror box 1 1/2 (not included) **Tube Bracket** 2 1/2 Wing knob - Two revolutions of knob releases tube bracket. To prevent stud from rotating, knob stays with mirror box use threaded insert, locknut or loctite Knob fits with Front view counterbore to provide a PRECISION ***Important*** without wing knob locked connection to the Threaded stud to extend mirror box Side view www.aurorap.com from mirror box by $\frac{5}{8}$ to $\frac{3}{4}$ for 6644 SE Jerry Dr. proper knob engagement Cut away showing knob Prineville Oregon 97754 Tube Bracket 1500 spec sheet, rev3 4-2-20 interlocked with tube Bracket

Drawings are to scale, dimension are inches

541-362-5965